

SQUARE PROJECTOR LIGHT



EST[®]
LIGHTS
Quality LED Solutions & Beyond



CREE ⇄






DALI/1-10V
Triac/PWM

CRI>80/90

IP66



Without Hood



Physical Dimension(MM)

MODEL NO.	POWER	LIGHT SOURCE	LED COLOR	BEAM ANGLE	INPUT VOLT	CONTROL
EST-D500102A	2.5W	1PCS OSRAM/CREE SMD	2200-6500K R/G/B/Y/A	5°/8°/10°/12°/ 20°/24°/36° /60°/10°*30°	AC110-240V	ON/OFF
EST-D500103A	2.5W/3W				DC12V/DC24V /DC36V/DC48V	ON/OFF /DMX512
EST-D500103B	3W	1PCS CREE/TYANSHINE SMD			AC110-240V	ON/OFF
EST-D500106A	3-6W				DC12V/DC24V /DC36V/DC48V	ON/OFF /DMX512
EST-D500106B	3-6W	1PCS TYANSHINE SMD	Turnable White 2700K/6500K	15°/25° /60°/ 15°*30°	DC12V/DC24V	DMX512
EST-D500101	1.5W		RGB 3in1			
EST-D500102B	2W		RGBW 4in1 (W: 2700K/3000K/4000K /5000K/5700K/6500K)			

Material Specifications

LED:CREE/OSRAM.


Housing:12# Die-casting powder coated aluminum.T=60-80µm

Adhesion of ISO class 1/ASTM class 48.


Gasket:Tooling shaped double silicone seal.

Dimmable: Triac/Dali/0-10V/PWM/DMX512.

Working Temperature:-20 to 40°C.



Cuboid hood Angle 25°



Cuboid hood

Features



High colour
rendering index



Excellent thermal
management



Dimmable versions
available



EMC-optimised