


SQUARE PROJECTOR LIGHT



CREE ⇄



DALI/1-10V
Triac/PWM

DMX



CRI>80/90

IP66


DMX512



Without Hood



Physical Dimension(MM)



MODEL NO.	POWER	LIGHT SOURCE	LED COLOR	BEAM ANGLE	INPUT VOLT	CONTROL
EST-D500103C	3W	1PCS CREE COB	2700K-6500K	15°/18°/34° (Reflector Cup)	AC110-240V	ON/OFF
EST-D500106C	3-6W				DC12V/DC24V /DC36V/DC48V	ON/OFF /DMX512
EST-D500103D	3W			15°/24°/36°/60° (Lens)	AC110-240V	ON/OFF
EST-D500106D	3-6W				DC12V/DC24V /DC36V/DC48V	ON/OFF /DMX512

Material Specifications

LED:CREE.


Housing:12# Die-casting powder coated aluminum.T=60-80µm

Adhesion of ISO class 1/ASTM class 48.


Gasket:Tooling shaped double silicone seal.

Dimmable: Triac/Dali/0-10V/PWM/DMX512.

Working Temperature:-20 to 40C.



Cuboid hood Angle 25°



Cuboid hood

Features



High colour
rendering index



Excellent thermal
management



Dimmable versions
available



EMC-optimised