

6500K 5700K 5000K 4000K 3500K 3000K 2700K

EST[®]
LIGHTS
Quality LED Solutions & Beyond



RGB 3 in 1



RGBW 4 in 1

CREE ⇄



DMX512 DC24V AC220V
IP68 Connector







DMX

DMX512

DALI/1-10V
Triac/PWM

CRI>80/90

IP66



MODEL NO.	POWER	LIGHT SOURCE	LED COLOR	BEAM ANGLE	INPUT VOLT	CONTROL
EST-D680106A	6W/8W /10W/12W	1PCS CREE/BRIDGELU X /CITILED COB	2700-6500K	15°/18°/34°/60° (Reflector Cup)	AC220-240V /AC110-240V	ON/OFF /Triac/0-10V
EST-D680108A	8W/12W				AC110-130V	Triac
EST-D680112A	6W-12W				DC24V/DC36V /DC48V	ON/OFF /Triac/0-10V /DALI/DMX512
EST-D680106B	6W/8W /10W/12W			15°/24°/36°/60° (Lens)	AC220-240V /AC110-240V	ON/OFF /Triac/0-10V
EST-D680108B	8W/12W				AC110-130V	Triac
EST-D680112B	6W-12W				DC24V/DC36V /DC48V	ON/OFF /Triac/0-10V /DALI/DMX512



Features



Graduations for
adjustability



Vertical Tiltable



Hinge lockable



Mounting plate
rotatable 355°



High colour
rendering index



Excellent thermal
management



Dimmable versions
available



Optional housing
colours